MILITARY STANDARD

ENVIRONMENTAL TEST METHODS

TO ALL HOLDERS OF MIL-STD-810B:

1. The following new method is to be added:

NEW METHOD		DATE
T519	Gunfire Vibration, Aircraft	29 September 1969

2. This U.S. Air Force Notice forms a part of MIL-STD-810B dated 15 June 1967. The general requirements of MIL-STD-810B shall apply to any application of this notice.

3. THIS NOTICE IS NONCUMULATIVE, RETAIN AND INSERT BEFORE THE TABLE OF CONTENTS.

4. Holders of MIL-STD-810B will verify above addition has been entered. This issuance, together with appended pages is a separate publication. Each notice is to be retained by stocking points until the Military Standard is completely revised or cancelled.

Custodian:
Air Force - 11

Preparing activity:
Air Force - 11

(Project No. MISC-F650)

FSC MISC

Source: https://assist.dla.mil -- Downloaded: 2026-11-08T00:58Z
Check the source to verify that this is the current version before use.

This tentative test method has been approved by the Department of the Air Force. It is optional for use by all activities.

METHOD T519

GUNFIRE VIBRATION, AIRCRAFT

1. Purpose. The gunfire vibration test is conducted to simulate the relatively brief but very intense vibration fields resulting from blast pressure fields generated by repetitive firing guns mounted in, on, or near the aircraft structure.

2. Apparatus. Vibration equipment with required instrumentation.

3. Criteria for application. The most severe vibration field results from blast pressure pulses coupling to the aircraft structure and inducing vibration fields that are of maximum intensity near the gun muzzle region. This field, designated by curve A on figure 519-1, decreases in an inverse relationship to the distance as viewed in a forward direction from the gun muzzle. The vibration field, designated by curve B on figure 519-1, decays similar to the primary field beginning at the gun muzzle and extending in the aft direction. This field, beyond the near field region of the muzzle, is of lower intensity. In no case should this test method be substituted for conventional vibration tests. Guns, physical locations, and ballistic parameters should be carefully and accurately identified prior to application of this test method. If the maximum test spectrum level of the gunfire configuration is equal to or less than .04 g^2/Hz, the gunfire method need not be conducted.

3.1 Sensitive equipment. Equipment found most susceptible to gunfire are those equipments that are usually located within a 3-foot radius of the gun muzzle and are mounted on the structural surface exposed to the gun blast. Prime examples are UHF antennas of the blade, V, and the flush-mounted configurations, including their bracketry, coaxial connectors, and lines. Next in order of failure susceptibility is equipment mounted on drop-down doors and access panels, equipment mounted in cavities adjacent to the aircraft surface, and finally, equipment located in the interior of the vehicle structure. Typical vulnerable equipment in these latter categories are auxiliary hydraulic and power units (including mounting bracketry), switches, relays, IR, photographic, communication and navigation equipment and radar systems, including items either shock or hard mounted.

3.2 Determination of test levels

3.2.1 Selection of the maximum test level. The maximum gunfire vibration level is defined by the following equation:

$$G_{max} = E_1/E_o(G_o/r_o n_o)\ (80/W_E)\ (r_1 n_1);\ \text{in PSD units } (g^2/Hz)$$

Source: https://assist.dla.mil -- Downloaded: 2026-11-08T00:58Z
Check the source to verify that this is the current version before use.

where: $80/W_E = 1$, for equipment weight $W_E \leq 80$ pounds

and: $80/W_E = 1/4$ for equipment weight $W_E \geq 160$ pounds

The test level (G_{max}) is obtained from the basic normalized level ($G_o/r_o n_o$) which is adjusted to the muzzle energy (E_1), the firing rate (r_1), and the number of guns (n_1) of the particular gun(s) under consideration. The normalizing energy (E_o) is equal to 39,600 foot-pounds. The last term ($80/W_E$) represents a mass adjustment factor and permits the reduction of G_{max} when the equipment weight is greater than 80 pounds. Table 519-1 designates the muzzle energies, the energy adjustment factors, and the nominal firing rates of commonly used gun configurations. Figure 519-1 provides $G_o/r_o n_o$ as a function of the distance parameter (D). The mass adjustment factor is determined from figure 519-2.

3.2.2 Determination of the distance parameter (D). The distance parameter represents the vector distance, measured (or estimated) from the gun muzzle to the mean distance between equipment support points. Where equipment support points are indeterminate, the equipment center of gravity shall represent the terminal point of D. The vector D is usually generated from the orthogonal distances referenced to the fuselage station, the water, and the butt line data. The D vector and the computation is shown on figure 519-3.

3.2.3 Multiple guns. For configurations involving multiple guns, the origin of D is determined from the centroidal point of the gun muzzles. Figure 519-4 shows the origin location for a typical four-gun staggered array.

Example No. 1 - A 2-pound UHF antenna, is to be flush mounted to the undersurface of the aircraft and located forward of the muzzle of four M-61 type cannons. The expected firing rate is 25 Hz ($r_1 = 25$). (If the firing rate is unknown, the maximum specified rate shall be used). Since, in this configuration, each barrel fires independently and the number of guns is equal to four, then $n_1 = 4$ (see 1/).

Steps

a. The antenna location determined from the aircraft spatial coordinates (see figure 519-3) is found to be 39 inches or D = 39 inches

b. Refer to Figure 519-1. Select curve A and obtain the ordinate value of $G_o/r_o n_o$ for D = 39 inches. In this case $G_o/r_o n_o = 3.0 \times 10^{-2}$

c. From table 519-I, select E_1/E_o for the M-61 gun (see 2/). Here, $E_1/E_o = 1$

Source: https://assist.dla.mil -- Downloaded: 2026-11-08T00:58Z
Check the source to verify that this is the current version before use.

d. Since the antenna weight is less than 80 pounds, the mass adjustment factor becomes unity and a reduction of G_{max} is not allowed (see figure 519-2)

e. Determine the normalized level, G_1/r_1n_1, by adjusting G_o/r_on_o by E_1/E_o as follows: $G_1/r_1n_1 = E_1/E_o\ (G_o/r_on_o)$ or $G_1/r_1n_1 = (1)\quad 3.0 \times 10^{-2}$

f. Multiply G_1/r_1n_1 by n_1r_1 to obtain the maximum test level, G_{max}:

$$G_{max} = G_1/r_1n_1\ (r_1n_1)$$

$$G_{max} = 3.0 \times 10^{-2}(10^2)$$

$$G_{max} = 3.0\ g^2/Hz$$

g. Apply G_{max} to figure 519-5 to obtain the test spectrum.

Example No. 2 - An electronic equipment weighing 102 pounds is located in the aircraft nose section forward of the gun muzzle. The distance (D) is 45 inches. The firing rate of the revolving barrels of the cannon totals 100 Hz with $n_1 = 1$. The muzzle energy (E_1) is 83,000 foot-pounds.

Steps:

a. Repeating steps (a) and (b) as before:
$G_o/r_on_o = 1.9 \times 10^{-2}$

b. From note 2, divide E_1/E_o:
$83 \times 10^3/39.6 \times 10^3 = 2.1$

c. Adjusting for E_1/E_o:
$G_1/r_1n_1 = (2.1)\ (1.9 \times 10^{-2})$
or $G_1/r_1n_1 = 4.0 \times 10^{-2}$

d. Obtain G_{max} as before:
$G_{max} = 4.0 \times 10^{-2}\ (10^2)\ (1) = 4.0\ g^2/Hz$

e. Noting from 3.2.1 that $W_E > 80$ pounds and referring to figure 519-2, where the derated value (G'_{max}) is found to be 2 dB down (-2 dB) from $4.0\ g^2/Hz$

Source: https://assist.dla.mil -- Downloaded: 2026-11-08T00:58Z
Check the source to verify that this is the current version before use.

From dB power tables:

$-2\ dB = LOG_{10}\ G'_{max}/4.0$

or $G'_{max} = 2.5\ g^2/Hz$

f. Apply G'_{max} to figure 519-5 to obtain the test spectrum.

1/ Some M-61 gun configurations (see MK-IV, gun pod, table 519-I) feature two barrels per pod; firing simultaneously. In such a case, $n_1 = 2$ per pod.

2/ If E_1 is unknown, determine E_1 from ballistic data using $E_1 = m_1 v_1^2/2$ where: m_1 = the projectile mass and v_1 = muzzle velocity. Divide by E_o (see table 519-I) and proceed as in step (e).

4. Test procedures. Test procedures used shall be as specified in the equipment specification or test plan.

4.1 Test item operation. Unless otherwise specified, the test item shall be operated during application of vibration so that functional effects caused by these tests may be evaluated. When a test item performance test is required during vibration and the time required for the performance is greater than the duration of the vibration test, the performance test shall be abbreviated accordingly. At the conclusion of the test, the test item shall be operated and the results compared with the data obtained in accordance with section 3, General Requirements, paragraph 3.2.1. The test item then shall be inspected in accordance with section 3, General Requirements, paragraph 3.2.4.

4.2 Mounting techniques. In accordance with section 3, General Requirements, paragraph 3.2.2, the test item shall be attached to the vibration exciter table by its normal mounting means or by means of a rigid fixture capable of transmitting the vibration conditions specified herein. Precautions shall be taken in the establishment of mechanical interfaces to minimize the introduction of undesirable responses in the test setup. Whenever possible, the test load shall be distributed uniformly on the vibration exciter table in order to minimize effects of unbalanced loads. Vibration amplitudes and frequencies shall be measured by techniques that will not significantly affect the test item input control or response. The input control accelerometer(s) shall be rigidly attached to the vibration table or to the intermediate structure, if used, at or as near as possible to the attachment point(s) of the test item.

5. Test procedures

5.1 Procedure I, Random vibration test. The test item shall be subjected to random vibration along each mutually perpendicular axis. Test times shall be in accordance with time schedule I from table 519-II. The instantaneous peaks of the random

Source: https://assist.dla.mil -- Downloaded: 2026-11-08T00:58Z
Check the source to verify that this is the current version before use.

vibration acceleration may be limited to 2.5 times the rms acceleration level. The power spectral density of the test level control signal shall not deviate from the specified requirements by more than +40 -30 percent (±1.5 dB) below 500 Hz and +100 -50 percent (±3.0 dB) between 500 and 2,000 Hz, except that deviations as large as +300 -75 percent (±6 dB) shall be allowed over a cumulative bandwidth of 100 Hz between 1,000 and 2,000 Hz for equipment items whose weight is equal to or less than 60 pounds. For items weighing more than 60 pounds, the same deviation shall be allowed over the extended range from 500 to 2,000 Hz provided the cumulative bandwidth deviation does not apply to the swept bandwidth of noise as detailed in 5.3.1.2.

5.2 Procedure II, Single direction test. If the equipment item is mounted with the base peripherally attached to and in the plane of the aircraft skin, then the test direction may be restricted to the direction normal to the aircraft skin (see figure 519-6). The total test time in this case shall be as stated in time schedule II of table 519-II.

5.3 Procedure III, Composite or alternate test. For locations near the gun muzzle and for equipment weighing in the region of 60 pounds, the test levels may exceed the force capabilities of all but the largest shaker systems. For such cases, the following test method may be substituted provided the following criteria are met:

when: $G_{max} \geq 3.0\ g^2/Hz \geq 8.6 \times 10^{-4}\ (F_r/W_T)^2$

where: $W_E \geq 55$ pounds and: $W_J \leq 1.2\ W_E$

F_r = Maximum RMS shaker force output - pounds

$W_T = W_E + W_A + W_J$

W_E = Equipment weight - pounds

W_A = Armature weight - pounds

W_J = Test jig weight - pounds

5.3.1 Selection of composite elements. A broad band, random vibration test level G_B shall be selected equal to $G_{max}/4$ (6 dB down). A random noise signal of 100 Hz bandwidth (3 dB down points) shall be superposed on G_B having a G_{max} equal to the original determined value. The composite spectrum is shown on figure 519-7.

5.3.1.2 Test procedure. The test shall be conducted in accordance with 5.1, except the narrow band noise shall be swept from 300 to 1,000 Hz, referenced to the narrow band center frequency. The sweep time shall be in accordance with time schedule III in table 519-II.

Source: https://assist.dla.mil -- Downloaded: 2026-11-08T00:58Z
Check the source to verify that this is the current version before use.

6. Test level overall rms. The overall rms test level shall be no less than the area enclosed by the solid curve of figure 519-5, -21 percent (-2 dB). The overall rms is defined by the following equation.

$$OAR = (1163\ G_{max})\ 1/2.$$

7. Summary. The following details shall be specified in the equipment specification or test plan:

a. Procedure number (see 5)

b. Pretest data required (section 3, General Requirements, paragraph 3.2.1)

c. Nonoperation of equipment during test, if desired (see 4.1)

d. Unique or special test considerations.

Source: https://assist.dla.mil -- Downloaded: 2026-11-08T00:58Z
Check the source to verify that this is the current version before use.




FIGURE 519-1. $G_o/n_o r_o$ vs. D

Source: https://assist.dla.mil -- Downloaded: 2026-11-08T00:58Z
Check the source to verify that this is the current version before use.





FIGURE 519-2. Reduction Factor for Mass Loading

Source: https://assist.dla.mil -- Downloaded: 2026-11-08T00:58Z
Check the source to verify that this is the current version before use.



$$D = \overline{OP} = (X^2 + Y^2 + Z^2)^{1/2}$$

FIGURE 519-3. Determination of the D Vector

Source: https://assist.dla.mil -- Downloaded: 2026-11-08T00:58Z
Check the source to verify that this is the current version before use.




FIGURE 519-4. Origin of the D Vector for Multigun, Staggered Array

Source: https://assist.dla.mil -- Downloaded: 2026-11-08T00:58Z
Check the source to verify that this is the current version before use.




FIGURE 519-5. Random Vibration Test Curve

Source: https://assist.dla.mil -- Downloaded: 2026-11-08T00:58Z
Check the source to verify that this is the current version before use.




FIGURE 519-6. Peripherally Mounted Item

Source: https://assist.dla.mil -- Downloaded: 2026-11-08T00:58Z
Check the source to verify that this is the current version before use.




FIGURE 519-7. Swept Random Vibration Test Curve

Source: https://assist.dla.mil -- Downloaded: 2026-11-08T00:58Z
Check the source to verify that this is the current version before use.

TABLE 519-I. Ballistic Table

Gun Configuration	Aircraft	Installation (Typical)	Gun Caliber (mm)	Gun Caliber (in)	Projectile weight (Gr)	Projectile weight (lbs)	Firing Rate (r_1) Rds/min Hz/min	Firing Rate (r_1) Rds/sec Hz/sec	Muzzle Velocity (V_1) (ft/sec)	Muzzle Energy (E_1) (ft-lbs)	Muzzle Energy of M-61 (E_o) (ft-lbs)	Energy Adjustment factor (E/E_o)
M61	F-104 F-105 F-111 F-4 F-100 B-58 B-52 A-7	Various Fixed (Forward Bomb Bay) SUU-16 on racks, tail turrets	20	.79	1,560 (avg)	.223 (avg)	6,000 (nom) 1,000 (min)	100 (max) 17 (min)	3,380 (nom) 3,250 to 3,450	39,600	39,600	1.0
M39	F-5 F-100 F-101 B-57 B-52	2 or 4 in nose or back of nose or tail turret	20	.79	1,560 (avg)	.223 (avg)	1,500	25	3,380 (nom) 3,250 to 3,450	39,600		1.0
MK11	A-4 F-4 A-7 A-6	MK4 C.L. POD inboard wing, etc.	20	.79	1,700	.243	2,500 (nom)	42	3,100	36,300		.918

Source: https://assist.dla.mil -- Downloaded: 2026-11-08T00:58Z
Check the source to verify that this is the current version before use.

TABLE 519-I. Ballistic Table (Continued)

MK12	A-4	1 at each wing root	20	.79	1,700	.243	1,000	16.68	3,300	41,200		1.04
M3	A-1E	2 each wing	20	.79	2,000	.286	800	13.33	2,700	33,400		.844
M24	B-52 F-86	Tail turret 4 or 6 nose	20	.79	2,000	.286	800	13.33	2,700	33,400		.844
M2		obsolete	12.7	.50	800	.114	750	12	2,800	13,900		.351
M3	B-52 B-26 B-57 F-86 HH-53 A-1	Tail turret up to 6 in nose	12.7	.50	709	.114	1,200 (nom)	20	2,810	12,430		.314
GAU-2B/A	AC-47 AC-130 A-37 UH-1 CH-3	side-looking, nose, and up to 8 PODS	7.62	.30	150	.021	6,000 (nom) 1,500 (min)	100 25 (min)	2,750	2,520		.0636

Source: https://assist.dla.mil -- Downloaded: 2026-11-08T00:58Z
Check the source to verify that this is the current version before use.

TABLE 519-II Random Vibration Test Time

TIME SCHEDULE	CYCLING TIME PER AXIS 1/ (MIN)	RANDOM TIME PER AXIS 1/ (MIN)	SWEEP TIME (MIN) 1/ 300-1,000-300 (Hz)
I	——	15	——
II	——	30	——
III	90	——	5

1/ The total test period may be subdivided into sequential vibration bursts between which cooling intervals are allowed. The burst time shall be no less than 60 seconds.

☆ U. S. GOVERNMENT PRINTING OFFICE: 1971-433-697/9213

Source: https://assist.dla.mil -- Downloaded: 2026-11-08T00:58Z
Check the source to verify that this is the current version before use.